

MODEL	CFM	Cooling Capacity				Heating Capacity			Elec.Consumption (W/Amp)	Dimensions		
		Total (Btu/hr)	Sensible (Btu/hr)	Water Flow (GPM)	P.D.(ft)	Capacity (Btu/hr)	Water Flow (GPM)	P.D.(ft)		L (mm)	W (mm)	H (mm)
DDFC-800	800	24800	19300	4.7	1.0	68800	4.7	1.9	350/1.7	480	600	450
DDFC-1000	1000	32750	24500	6.2	1.7	87500	6.2	2.1	350/1.7	520	600	450
DDFC-1200	1200	41500	30500	7.8	2.0	101300	7.8	2.6	450/2.2	650	600	450
DDFC-1400	1400	50000	36000	9.0	2.5	118498	9.0	3.36	450/2.2	700	600	450
DDFC-1600	1600	60000	41000	9.8	2.53	135100	9.8	4.1	2*(350/1.7)	830	600	450
DDFC-1800	1800	70500	49300	11.0	2.57	153650	11.0	3.7	2*(350/1.7)	880	600	450
DDFC-2000	2000	81000	55000	12.3	2.64	173850	12.3	4.8	2*(450/2.2)	1060	600	450
DDFC-2400	2400	92000	66000	18.0	2.94	223000	18.0	8.5	2*(450/2.2)	1200	600	450

مجهز به فن فلزی - صدای بسیار کم - الکترو موتور ۳ سرعتی - فیلتر پارچه ای پروپیلن
سایز اتصالات ورود و خروج آب به دستگاه در تمام ظرفیتهای 1,1/4" میباشد.
سایز لوله درین دستگاه 1/2" میباشد.



Metal



LOW

Elec. Motor
3SpeedSynthetic
Filter

فن کویل کانالی

Ducted
Fan coil